





Decontamination Accessories			
	TVI No.	Nomenclature	Description
Water & Plumbing			
	WH-340-1-1	Flash Water Heater w/ Solution Injector	Flash Water Heater Injection System, 340,000 btu / hr, 11 gpm 40 degree delta T System includes multi fuel fired Flash Heater with Solution Injector, Pressure Reducing Valve, Temperature Valve, and Electronic Burner Thermostat. Unit is Man portable with turf wheels and guide handles.
	WH-500-2-1	Flash Water Heater w/ Solution Injector	Flash Water Heater Injection System, 500,000 btu / hr, 20 gpm 40 degree delta T System includes multi fuel fired Flash Heater with Solution Injector, Pressure Reducing Valve, Temperature Valve, and Electronic Burner Thermostat. Unit is Man portable with turf wheels and guide handles.
	WP-18-S	Waste Water Pump	Submersible 18GPM waste water pump constructed of non-conductive materials. Pumps within 1/8" of the floor, allowing for more complete waste water removal. The motor features a thermal overload protector and a screen base for anti-silt operations. 15 Ft rapid-connect discharge hose transports wastewater to a collection basin or bladder.
	FR-24-48	Floor Risers	Keeps First Responders and ambulatory patients above the waste water. Black, rigid, corrosion resistant polyethylene material (2'W x 4'L x 1 _"HR) Resistant to acids, salt, gasoline, petroleum products, solvents and most chemicals.
	HW-D20B-.50-CFCF (Blue) HW-D20C-.50-CFCF (Red) HW-D50B-.75-CFCF (Blue) HW-D50C-.75-CFCF (Red)	Decon Hoses	Decon, Nylon F-F Camlocks, 20ft, Blue, 1/2" Decon, Nylon F-F Camlocks, 20ft, Red, 1/2" Decon, Nylon F-F Camlocks, 50ft, Blue, 3/4" Decon, Nylon F-F Camlocks, 50ft, Red, 3/4"
	BW-0250-R BW-0500-R BW-1000-R BW-2000-R	Storage Bladder - 250 gal 500 gal 1000 gal 2000 gal	Water Bladder. Constructed of HD Polymer and features a corner drain for convenient discharge.
	HB-156-240-E	Berm	Berm for temporary waste water containment. Chemically resistant high performance reinforced elastomer membrane.
Patient Transfer & Non Ambulatory			
	HS-X-P	Hand Sprayers	The high performance hand sprayers features quick-connectors, a 3/8" x 9/16" poly-coiled hose and are tested at .63GPM @ 3200psi, providing an 80 degree fan pattern. Also features automatic shut-off and twist-off nozzles for easy cleaning.

	<p>LC-1812-X LC-1810-X LC-1812-X</p>	<p>8' Litter Conveyor 10' Litter Conveyor 12' Litter Conveyor</p>	<p>Rapidly deployable, lightweight and rugged. The conveyor system features quick deployment/redeployment (collapses quickly into a compact package for stowage or transport); articulating frame expands into sturdy table with built-in roller devices. Conveyor and Board resist corrosion and are easily decontaminated. Features locking mechanisms for connecting multiple sections; load capacity over 300 pounds per linear foot. (anodized scissor-frame sections are constructed of high grade, light-weight structural aluminum)</p>
	<p>LCA-B</p>	<p>Transfer Board</p>	<p>20"W x 8'L Transfer Board affords safe and efficient casualty handling. Constructed of rugged polypropylene creating a load capacity over 300 pounds per linear foot and with guides to keep transfer board aligned on conveyor</p>
Air & Lighting			
	<p>AH-150-15</p>	<p>Forced Air Heater</p>	<p>150K BTU, diesel-fired air heater capable of providing clean heated fresh air to enclosed shelters for casualty warming/comfort. The combustion chamber uses a stainless steel heat exchanger that separates combustion gases (exhaust) from the fresh heated air (shelter air). The heater Features rugged construction, man-portable wheels and guide handle, thermostatic temperature control and a removable exhaust stack for convenient storage. (Integrated 13.5 Gal fuel tank allows for approximately 13 hours of continues operation)</p>
	<p>LF-40-1</p>	<p>Lights Fixtures</p>	<p>NEMA 4X watertight plug and connector, 40W, 110V fluorescent light constructed of heavy duty plastic shields with neoprene end caps (water and vapor resistant). Includes hanging clips, 15ft yellow SJOW cord, with connector for ganging lights in series.</p>